



Name of Chassis

Car Approval Check List

	ITEM	YES	NO	N/A	Comments
1	Belly Pan Steel (min. 0.025" thickness)				
2	Belly Pan Aluminum (min. 0.040" thickness)				
3	All edges on body and tailcone are rounded				
4	Maximum Height of Body is 28"				
5	Maximum Height of Side Panel is 22"				
6	Bumpers				
6a	Secured with bolts 6-32 to 10-32, No slotted screws, machine screws or pan head screws				
6b	Top and bottom bumper tubes mounted over each other				
6c	Steel construction, minimum 5/8", 0.049"				
7	Firewall (steel- 0.025" or aluminum- 0.048" thickness)				
8	Frame - SAE 4130 Steel (chromium molybdenum)				
9	Fuel Tank (min. 0.050" aluminum, no steel tanks, max. 140 ounces)				
10	Nerf Bar				
10a	Secured with bolts 6-32 to 10-32, No slotted screws, machine screws or pan head screws				
10b	Steel construction, minimum 5/8", 0.049"				
11	All Radius rods, locating rods constructed of Aluminum, No exotic materials				
12	Roll Cage (must be of down tube design)				
12a	If <=34" in height, minimum 3/4" O.D., 0.058" SAE 4130				
12b	If > 34" in height, minimum 3/4" O.D., 0.058" SAE 4130				
12c	If side bars, minimum 5/8" O.D., 0.049" SAE 4130				
13	Shoulder Bar				
13a	Steel construction, minimum 5/8", 0.049"				
13b	Stainless, minimum 5/8" O.D., 0.065" or /16 gauge				
13c	Welded				
13d	Attached with bolt, 8-32 - 10-32, No slotted screws, machine screws or pan head screws				
14	Switch mount located inside drivers compartment				
15	Mig Welded/Tig Welded				
15a	Other by approval				

Signature/Date

Approval Signature/Date

Print Name

Approval Print Name

Position

Send Completed Copy to National Safety Director Via email and signed hard copy via postal service. Once approved, a signed copy will be returned to you.